		Į:	sola	atior	n Blir	nd Lis	st (Sup	plemental)	)			Isolation Blind List (Supplemental)														
Unit:   Equipment No:   Equipment Description:   Lockbox No. / Location:														Sheet #	of											
LOCKBOX	10.7 Location.				Blind Is	solation	Identifica	ation																		
Blind Tag	Description of Blind Location	Class	Туре	Size	Rating	Cooket	Operating Position	Fresh Air Possibly Required (Refer to Permit)	Tag Staged Initial / Date	Installation		Removal		Change Log/ Temporary Release												
No.	Description of Billid Location	Blind	of Blind							Servicing Initial / Date	Owner Initial / Date	Servicing Initial / Date	Owner Initial / Date	Number	Initials											
								©YES ○NO																		
								CYES CNO																		
								CYES CNO																		
								CYES CNO																		
								CYES CNO																		
								CYES CNO																		
								CYES ONO																		
								CYES CNO																		
								CYES CNO																		
								CYES CNO																		
								CYES CNO																		
								CYES CNO																		
								CYES CNO																		
								CYES ONO																		
								CYES CNO																		
			-		_			CYES ONO																		
			-			-		CYES CNO																		
								CYES CNO																		
								CYES ONO						-												
			-			-		CYES ONO																		
			_		_			CYES ONO																		
		_	-					CYES CNO						-												
			-					CYES CNO																		
					_			CYES CNO																		
			-	-	-	1		CYES CNO					1													
					-			CYES ONO																		
Notes		Dline	Turna				BAB - Babir			L	Gaskets															
No blind or plug to be installed without a tag.		Blind	I <b>ype</b> Spec B	امسا						SSIR - Graphoil Filled 316SS Spiral Wound with Inner Ring																
								ble Block and Bleed																		
Tags to be installed and removed by operators only.			SL - Slip Blind MG - Mech								321SSIR - Graphoil Filled 321SS Spiral Wound with Inner Ring															
Tags to be installed to indicate intended flange or plug			B P - Break and Plug ES - Electrical Switch Gear								347SSIR - Graphoil Filled 347SS Spiral Wound with Inner Ring															
locations but not to interfere with blind or plug installation.			B - Break Open HMR - Hammer Blind								MONEL IR - Graphoil Filled Monel Spiral Wound with Inner Ring															
4. "Blind or plug in" and "Blind or plug out" are not to be												A20 IR - Graphoil Filled Alloy 20 Spiral Wound with Inner Ring														
initialed until operator has personally inspected location.  5. Thin blinds can be used on Alky Reactors and			SPCR - Spacer Blind VB - Vented Blind									APX2 - Service above 850 Degrees														
Alky Acid Settlers.											Class Blind Operating Position															
·y ·z			TB - Thin Blind								1 - Isolation															
												ntry, Hot Work O - Blind or Plug Out														
			DED BOY EUR BINNE									or Line Break														